

# Ojo-Ojo



Cable Centro Acero. Diámetro en Pulgadas.	Capacidad nominal en toneladas			Dimensión Estandar del Ojo		Dimensiones Ojo dedal Alta Resistencia		Longitud Mínima del Cabestrillo
	Eganche Vertical	Eganche Gargantilla	Eganche de Cesta Vertical	A"	L"	A"	L"	
1/4"	0.65	0.48	1.3	2"	4"	7/8"	1-5/8"	1'6"
5/16"	1	0.74	2	2-1/2"	5"	1-1/16"	1-7/8"	1'9"
3/8"	1.4	1.1	2.9	3"	6"	1-1/8"	2-1/8"	2'
1/2"	2.5	1.9	5.1	4"	8"	1-1/2"	2-3/4"	2'6"
9/16"	3.2	2.4	6.4	4-1/2"	9"	1-1/2"	2-3/4"	2'9"
5/8"	3.9	2.9	7.8	5"	10"	1-3/4"	3-1/4"	3'
3/4"	5.6	4.1	11	6"	12"	2"	3-3/4"	3'6"
7/8"	7.6	5.6	15	7"	14"	2-1/4"	4-1/4"	4'
1"	9.8	7.2	20	8"	16"	2-1/2"	4-1/2"	4'6"
1-1/8"	12	9.1	24	9"	18"	2-7/8"	5-1/8"	5'
1-1/4"	15	11	30	10"	20"	2-7/8"	5-1/8"	5'6"
1-3/8"	18	13	36	11"	22"	3-1/2"	6-1/4"	6'
1-1/2"	21	16	42	12"	24"	3-1/2"	6-1/4"	7'
1-3/4"	28	21	57	14"	28"	4-1/2"	9"	8'
2"	37	28	73	16"	32"	6"	12"	9'